



# Single Axis Co-Locating Mount for Cisco 3800 Access Point and Wi-Fi Antennas

Ventev's Single-Axis Co-Locating Mount for Cisco 3800 access point (AP) and antennas simplifies deployments, improves network performance, and presents an aesthetically pleasing appearance. *Every TerraWave product is RoHS compliant, and is covered by Ventev's two-year TerraNet warranty program. For more information contact Ventev: 800-851-4965 or sales@ventev.com.*



Co-Locating Mounts in University of Missouri lecture hall

### Features and Benefits

- Installs AP and antenna together, making it an ideal choice for difficult locations such as high ceilings
- Eliminates long cable runs between AP and external antenna for reduced signal attenuation
- Antenna mounting tray articulates +/- 55 degrees for precise beam positioning
- Conceals the AP and cables
- Compatible with Cisco's 2802e/3802e APs
- Ideal for Auditoriums, Convention Centers, Aisles in Industrial Venues

Specifications	
Model	TW-COLOMOUNT-1
Dimensions	9.5" X 10.25" X 4.75"
Weight	2.5 lbs
Material	Powder-Coated Aluminum
Operating Temperature Range	-4° F to +131° F
Compatible TerraWave Antennas	
349502, 515085, 515086, 510701, 215098	
Compatible Cisco Antennas	
AIR-ANT-2566P4W-R	A TerraWave Adapter Plate (SKU 518506 or 574960) is required to mount the Cisco Antenna to the Co-Locating Mount.
AIR-ANT-2566D414-R	A TerraWave Adapter Plate (SKU 553852) is required to mount the Cisco Antenna to the Co-Locating Mount.

Ventev's Single-Axis Co-Locating Mount is a Patented Design