

802.11n/ac Quad Patch Antenna with RPTNC Plugs (Fits Cisco Co-Locating Mount)

This 2.4/5 GHz 6 dBi directional antenna features four dual-band antennas in a single unit. Each antenna pigtail is dual-band with RPTNC Plugs. This antenna allows wireless engineers to simplify deployments by using only one antenna for dual band access points. Deployment is further simplified by the multiple mounting options: the antenna ships with TerraWave's Universal Articulating Mount (SKU 384807), and the back panel hole patterns are also compatible with TerraWave's Cisco Co-Locating Mount (SKU 568600) (sold separately). *Every TerraWave antenna is covered by the company's two-year TerraNet warranty program. For questions or to purchase product, contact your Regional Sales Executive at 210-375-8482, 800-851-4965 or sales@terra-wave.com.*



Specifications		
Model	M6060060P1D43602M	
Frequency Range	2400~2500	5150~5850
Bandwidth	100 MHz	700 MHz
Gain	6 dBi	6dBi
Horizontal Beamwidth	105	125
Vertical Beamwidth	60	70
VSWR	≤2.0	≤2.0
Isolation	≥20dB	
Nominal Impedance	50 Ohm	
Polarization	Vertical	
Maximum Input Power	20 W	
Lightning Protection	N/A	
Connector Type	4x RPTNC Plug	
Cable Length	36"	
Dimensions	10" x 5.6" x 1.4"	
Weight	1.2 lbs	
Operating Temperature	-40°F to 158°F	
Wind Load	60 mph	

2410 MHz





5250 MHz

H Plane

E Plane

H Plane

E Plane



802.11n/ac Quad Patch Antenna with RPTNC Plugs (Fits Cisco Co-Locating Mount)

Mounting Bracket Information

Installation Instructions:

1. Place the bracket on the back of the panel antenna. Attach the antenna to the mast.
2. Use the client to test and adjust the receive signal strength (RSSI) and adjust the azimuth and elevation to maximize the RSSI. Tighten each nut and seal the antenna connector.

