

## Specifications

- UL approved for direct burial or sunlight applications
- Tinned copper braid and aluminum tape with drain wire
- 600 volts power tray cable
- Available per foot or bulk
- Labeled per ICEA standards
- Other wire colors available



Cable Type	Comp A	Comp B	Overall Cable	Nominal OD (inches)	Description	Part Number
7/C Composite	6/C 8 168/30 TC, .032 PVC, .006 Nylon	1/C 10 105/30 BC Ground Wire - Uninsulated	M/A Foil, 12 65/30 TC DW, 36 TC BS - 85%, .085 PVC JKT	.910	8-AWG, 6-conductor shielded, #8 tinned copper with #10 bare ground wire	86CS-8MC-10
3/C Composite	2/C 12 65/30 TC, .016 PVC, .005 Nylon	1/C 12 65/30 BC Ground Wire - Uninsulated	M/A Foil, 14 41/30 TC DW, 36 TC BS - 85%, .050 PVC JKT	.395	12-AWG, 2-conductor shielded, #12 AWG 65 strands tinned copper with #12 bare ground wire	122CS-12RB-12



Available through



Cables Unlimited  
Division of RF Industries  
(800) 590-9965 (631) 563-6363  
www.cables-unlimited.com  
quotes@cables-unlimited.com



RF Cable Assembly  
Division of RF Industries  
(800) 233-1728 (858) 549-6340  
www.rfcables.com  
rfi@rfindustries.com