

Series 88+

General Specifications

SCADA Ready Photovoltaic Power Systems

THE NEW VALUE FRONTIER



GENERAL SPECIFICATIONS:

- Solar Panels
 - 10 watt to 20 watt
 - 10 year warranty
 - 40 watt to 130 watt
 - Kyocera UL certified panels, Class I Division II
 - 20 year warranty
 - Solar array cable and 15' conduit assembly included with panels
- Panel Mounting Structure
 - Side-of-pole mounting structure – adjustable tilt
 - Fits 2" – 4" schedule 40 pipe; mounting hardware included
- Enclosure
 - NEMA 4X, Class I Division II, Groups A,B,C & D
 - Stainless steel hardware; padlock latch; integrated mounting flange for 2" – 4" schedule 40 pipe
 - DIN rail mounting for radios, RTU or other hardware
 - (4) Fuses, DIN rail mounted for solar array, battery, and (2) load for NEC compliance
 - Battery charge controller 0-10 amps, DIN rail mounted with low voltage disconnect
- Battery – 12 volt (nominal) sealed GEL battery – maintenance free
- System wiring, grounding terminal, and hardware installed
- System documentation package

OPTIONS:

- SNMP web card with battery test capability for remote system monitoring
- DIN rail mounted universal bracket for MDS, Raven X and other panel mounted radio units
- Optional back plates and shelves available for various radio mounting configurations
- Single and dual DIN rail mounted Power over Ethernet (PoE) kits
- Coaxial lightning and surge protection, internally mounted
- 24VDC to 48VDC PoE Module
- 5 Port Unmanaged Switch
- Door switch
- Utility pole mounting kits for 4" to 13.5" OD pipes or wood poles

Please contact TESCO Technologies, Inc for pricing

CUSTOM ENGINEERED SOLUTIONS AVAILABLE

Effective June 12, 2009

www.tesco.com/go/solar

Series 88+

General Specifications

SCADA Ready Photovoltaic Power Systems

THE NEW VALUE FRONTIER



System Part Number	TESSCO SKU	Module (Watts)	Battery Type	System Voltage	Enclosure Size	Enclosure Type	Enclosure Rating
602422	373371	10	18 AH	12 Vdc	12" x 10" x 6"	Fiberglass	NEMA 4X
602423	373918	20	18 AH	12 Vdc	12" x 10" x 6"	Fiberglass	NEMA 4X
602432	314092	20	2 x 7AH	12 Vdc	12" x 10" x 6"	Fiberglass	NEMA 4X
602424	303848	40	18 AH	12 Vdc	12" x 10" x 6"	Fiberglass	NEMA 4X
602425	393593	20	36 AH	12 Vdc	12" x 10" x 6"	Fiberglass	NEMA 4X
602426	303688	40	36 AH	12 Vdc	12" x 10" x 6"	Fiberglass	NEMA 4X
602451	343792	10	36 AH	12 Vdc	18" x 16" x 12"	Aluminum	NEMA 4X
602452	393089	20	36 AH	12 Vdc	18" x 16" x 12"	Aluminum	NEMA 4X
602446	333797	40	36 AH	12 Vdc	18" x 16" x 12"	Aluminum	NEMA 4X
602386	353740	40	84 AH	12 Vdc	26" x 16" x 12"	Aluminum	NEMA 4X
602387	393138	50	84 AH	12 Vdc	26" x 16" x 12"	Aluminum	NEMA 4X
602400	393696	65	84 AH	12 Vdc	26" x 16" x 12"	Aluminum	NEMA 4X
602382	313142	40	99 AH	12 Vdc	26" x 16" x 12"	Aluminum	NEMA 4X
602383	363550	50	99 AH	12 Vdc	26" x 16" x 12"	Aluminum	NEMA 4X
602390	393145	65	99 AH	12 Vdc	26" x 16" x 12"	Aluminum	NEMA 4X
602384	315157	85	99 AH	12 Vdc	26" x 16" x 12"	Aluminum	NEMA 4X
602385	373522	130	99 AH	12 Vdc	26" x 16" x 12"	Aluminum	NEMA 4X
602388	333610	85	198 AH	12 Vdc	26" x 27" x 12"	Aluminum	NEMA 4X
602389	383459	130	198 AH	12 Vdc	26" x 27" x 12"	Aluminum	NEMA 4X

Effective June 12, 2009

www.tessco.com/go/solar